

Twoja Infrastruktura IT

netf.pl

NETF, specjalizujemy się w sprzedaży zaawansowanej infrastruktury IT. Znajdą tu Państwo szeroki asortyment produktów od czołowych światowych producentów sprzętu i oprogramowania IT, w tym H3C, Huawei, Cisco, Juniper, Fortinet, a także Dell, IBM, CommVault i ESET. Dzięki współpracy z tymi renomowanymi partnerami, NETF zapewnia swoim klientom dostęp do najnowocześniejszych rozwiązań technologicznych.

**Bezpieczeństwo,
Efektywność,
Optymalizacja**



1200 Series Firewall

Enterprise Security Appliances



Contents

Product overview	3
Feature highlights.....	4
Performance	6
Scalability.....	7
Hardware specifications.....	8
Compliance	9
Ordering information	10
Cisco Capital	11

Product overview

The Cisco Secure Firewall 1200 Series is a family of security appliances that serves to connect and protect the distributed enterprise. It extends Cisco's enterprise security policy and threat inspection to users and devices in branch offices and smaller sites. Powered by an efficient network processor, 1200 Series delivers high levels of security policy and threat defense without compromising user experience.

Table 1. 1200 Series Models Summary

Model	Form factor	Firewall Throughput	Threat Defense	IPS Throughput	Interfaces
1210CE	Desktop/ Compact	6.5 Gbps	6.0 Gbps	6.0 Gbps	8x 1000BASE-T Gigabit Ethernet (10/100/1000 Mbps)
1210CP	Desktop/ Compact	6.5 Gbps	6.0 Gbps	6.0 Gbps	8x 1000BASE-T Gigabit Ethernet (10/100/1000 Mbps) 4 ports with PoE delivering up to 120W
1220CX	Desktop/ Compact	15 Gbps	9.0 Gbps	9.0 Gbps	8x 1000BASE-T Gigabit Ethernet (10/100/1000 Mbps) 2x SFP+ 10Gbps Ethernet



Figure 1. Cisco Secure Firewall 1210CE



Figure 2. Cisco Secure Firewall 1210CP



Figure 3. Cisco Secure Firewall 1220CX

Feature highlights

1200 Series firewalls are available with Cisco Adaptive Security Appliance (ASA) or Cisco Secure Firewall Threat Defense (FTD) software. For full details on the features supported in these applications, please refer to the software release documentation.

Table 2. 1200 Series with Threat Defense Software Features

Features	Details
Trust and Integrity	Built with Cisco Trustworthy Technologies to provide a hardware root of trust, cryptographically signed and validated software image support, anti-tamper and anti-counterfeit
High availability (HA)	Support for active/standby HA pairs
Multi-Instance	Not supported
Network security management	Centralized management via Cisco Secure Firewall Management Center (FMC) On-box management via Cisco Secure Firewall Device Manager (FDM) Cloud-managed via Cisco Security Cloud Control (SCC, formerly CDO)

Table 3. 1200 Series Hardware Features

Features	Details
Form factor	Compact appliance for desktop use. Can be rack-mounted or wall-mounted via optional accessories
Console port	USB Type-C and RJ-45 (Cisco serial)
Management Ethernet	1000BASE-T port
USB port	USB 3 Type A port
Storage	Integrated SSD, 480GB

Features	Details
Power supply	Single input, external power supply
Cooling	Integrated blower, side exhaust
Power over Ethernet (1210CP model only)	4 of the 1000BASE-T ports support IEEE 802.3at for delivery of up to 30W per port (120W total) to compatible PD endpoints
SFP+ transceiver slots (1220CX model only)	Support for a wide range of 1Gbps and 10Gbps transceivers. For a full list, refer to the product hardware documentation and Cisco's transceiver compatibility matrix tools

Table 4. 1200 Series interfaces

Metric	1210CE	1210CP	1220CX
Integrated interfaces	8x 1000BASE-T	8x 1000BASE-T	8x 1000BASE-T
Transceiver slots	-	-	2x SFP+
Power over Ethernet	-	4 ports, 120W total	-

Performance

1200 Series firewalls are powered by an advanced processor that accelerates security and networking functions.

Note: Performance will vary depending on features activated, network traffic protocol mix, and packet size characteristics. Performance is subject to change with new software releases. Consult your Cisco representative for detailed sizing guidance.

Table 5. Performance - 1200 Series with Threat Defense software

Metric	1210CE	1210CP	1220CX
Throughput: FW + AVC (1024B)	6.0 Gbps	6.0 Gbps	9.0 Gbps
Throughput: Next-Generation Intrusion Prevention System (NGIPS) (1024B)	6.0 Gbps	6.0 Gbps	9.0 Gbps
Throughput: FW + AVC + IPS (1024B)	6.0 Gbps	6.0 Gbps	9.0 Gbps
IPSec VPN Throughput (1024B TCP w/Fastpath)	5.0 Gbps	5.0 Gbps	10 Gbps
TLS (Hardware Decryption)	1.0 Gbps	1.0 Gbps	1.5 Gbps
Maximum new connections per second, with AVC	35K	35K	50K

Table 6. Performance - 1200 Series with ASA software

Metric	1210CE	1210CP	1220CX
Stateful inspection firewall throughput ¹	6.5 Gbps	6.5 Gbps	15 Gbps
Stateful inspection firewall throughput (multiprotocol) ²	6.0 Gbps	6.0 Gbps	12 Gbps
IPsec VPN throughput (450B UDP L2L test)	5.5 Gbps	5.5 Gbps	12 Gbps
New connections per second	175K	175K	250K

Note: Performance will vary depending on features activated, network traffic protocol mix, and packet size characteristics. Performance is subject to change with new software releases. Consult your Cisco representative for detailed sizing guidance.

¹ Throughput measured with 1500B User Datagram Protocol (UDP) traffic measured under ideal test conditions.

² "Multiprotocol" refers to a traffic profile consisting primarily of TCP-based protocols and applications such as HTTP, SMTP, FTP, IMAPv4, BitTorrent, and DNS.

Scalability

1200 Series appliances are designed for deployment in branch offices and smaller sites.

Table 7. Scalability - 1200 Series with Threat Defense software

Measure	1210CE	1210CP	1220CX
Maximum concurrent sessions, with AVC	200K	200K	300K
Maximum VPN Peers	200	200	300
Maximum virtual router instances (VRF)	5	5	10

Table 8. Scalability - 1200 Series with ASA software

Measure	1210CE	1210CP	1220CX
Concurrent firewall connections	200K	200K	300K
Maximum VPN Peers	200	200	300

Hardware specifications

Table 9. 1200 Series hardware specifications

Specification	1210CE	1210CP	1220CX
Chassis Dimensions (HxWxD) Excluding rubber feet	1.11" x 10.8" x 6.8" 2.82 x 27.43 x 17.22 cm		
Weight	3.04 lb (1.38 kg)	3.17 lb (1.44 kg)	3.09 lb (1.40 kg)
Operating range			
Temperature: operating	32 to 104°F (0 to 40°C) ³		
Humidity: operating	5 to 85% (noncondensing)		
Altitude: operating	0 to 10,000 ft (3048 m)		
Acoustic noise	23.5 dBA @ 80.6°F(27°C) 42.7 dBA @ maximum fan speed		
Non-operating/storage environment			
Temperature: nonoperating	-13 to 158°F (-25 to 70°C)		
Humidity: nonoperating	5 to 95% (noncondensing)		
Altitude: nonoperating	0 to 15,000 ft (4570 m)		
Power supply			
AC input voltage	100-240V AC		
AC input frequency	50-60 Hz		
AC current draw, maximum	0.4A (100V) 0.17A (240V)		
Power consumption, typical			
Power consumption, maximum	40W	40W (excluding PoE) 165W (including PoE)	40W

³ Derate the maximum operating temperature 2.7° F (1.5° C) per 1000 ft (304 m) above 6,000 ft (1829 m) altitude.

Compliance

For details on product regulatory compliance in a specific market, consult the Cisco [Product Approvals](#) tool.

Table 10. 1200 Series Regulatory and Standards Compliance

Specification	Description
Regulatory compliance	Products comply with CE markings per directives 2004/108/EC and 2006/108/EC
Safety	<ul style="list-style-type: none"> • UL 60950-1 • CAN/CSA-C22.2 No. 60950-1 • EN 60950-1 • IEC 60950-1 • AS/NZS 60950-1 • UL 62368-1 • CAN/CSA-C22.2 No. 62368-1 • EN 62368-1 • IEC 62368-1 • AS/NZS 62368-1
EMC: Emissions	<ul style="list-style-type: none"> • 47CFR Part 15 (CFR 47) Class A (FCC Class A) • AS/NZS CISPR22 Class A • CISPR22 Class A • EN55022 Class A • ICES003 Class A • VCCI Class A • EN61000-3-2 • EN61000-3-3 • KN22 Class A • CNS13438 Class A • EN300386 • TCVN7189
EMC: Immunity	<ul style="list-style-type: none"> • EN55024 • CISPR24 • EN300386 • KN24 • TVCN 7317 • EN-61000-4-2, EN-61000-4-3, EN-61000-4-4, EN-61000-4-5, EN-61000-4-6, EN-61000-4-8, EN61000-4-11

Ordering information

1200 Series hardware appliances and accessories are listed below. For information on licenses, subscriptions and other options associated with the product, refer to the [Network Security Ordering Guide](#).

Table 11. 1200 Series Firewall Appliances

Product ID	Description
CSF1210CE-ASA-K9	Secure Firewall 1210 compact security appliance with ASA software
CSF1210CE-TD-K9	Secure Firewall 1210 compact security appliance with Threat Defense software
CSF1210CP-ASA-K9	Secure Firewall 1210 compact security appliance with PoE, ASA software
CSF1210CP-TD-K9	Secure Firewall 1210 compact security appliance with PoE, Threat Defense software
CSF1220CX-ASA-K9	Secure Firewall 1220 compact security appliance with ASA software
CSF1220CX-TD-K9	Secure Firewall 1220 compact security appliance with Threat Defense software

Table 12. 1200 Series Accessories

Product ID	Description
CSF1200C-PWR-AC	Secure Firewall 1200 Series Compact power supply (without PoE)
CSF1200CP-PWR-AC	Secure Firewall 1200 Series Compact power supply (with PoE)
CSF1200C-RACK-MNT=	Secure Firewall 1200 Series Compact appliance rack-mount kit (compact models)
CSF1200C-WALL-MNT=	Secure Firewall 1200 Series Compact appliance wall-mount kit (compact models)
CAB-CONS-USB-C=	Console cable, USB-C to USB-C, 6ft, compatible with 1200 Series firewalls



Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more.](#)