

Twoja Infrastruktura IT

netf.pl

NETF, specjalizujemy się w sprzedaży zaawansowanej infrastruktury IT. Znajdą tu Państwo szeroki asortyment produktów od czołowych światowych producentów sprzętu i oprogramowania IT, w tym H3C, Huawei, Cisco, Juniper, Fortinet, a także Dell, IBM, CommVault i ESET. Dzięki współpracy z tymi renomowanymi partnerami, NETF zapewnia swoim klientom dostęp do najnowocześniejszych rozwiązań technologicznych.

**Bezpieczeństwo,
Efektywność,
Optymalizacja**





GigaBeam



The GigaBeam™ is an airMAX® 60 GHz radio designed for low-interference and high-throughput connectivity of up to 1+ Gbps. For the 60 GHz link, the GigaBeam supports full bandwidth use of 2.16 GHz and includes a 5 GHz radio for failover. The dedicated management radio allows easy setup via Wi-Fi.

Mechanical

Dimensions	Ø140 x 44 mm (Ø5.5 x 1.7")
Weight	376 g (13.3 oz)
Enclosure Characteristics	UV Resistant Polycarbonate

Hardware

Processor	Quad-Core ARM Cortex A7
Memory	256 MB DDR3
Networking Interface	10/100/1000 Mbps Ethernet RJ45
RF Connections	Internal
LEDs	Power/Ethernet/5G/60G
Max. Power Consumption	11W
Power Method	Passive PoE (Pairs 4, 5+; 7, 8-)
Power Supply	24VDC, 0.5A Gigabit PoE Adapter
Supported Voltage Range	24V ±10% (22 - 26VDC)
ESD/EMP Protection	Air/Contact: ± 24kV
Operating Temperature	-40 to 60° C (-40 to 140° F)
Operating Humidity	5 - 95% Noncondensing
Certifications	FCC, IC, CE

Software

OS	airOS®
Operating Modes	PtP
Ubiquiti Specific Features	Integrated 60 GHz and 5 GHz Radios, Discovery Protocol
Security	WPA2 AES Only
Dashboard	Yes
Wireless Settings	Yes
Network Settings	Yes
System	Yes
Services	UNMS, Ping Watchdog, Web Server, SSH Server, NTP Client, System Log, Device Discovery
Tools	Antenna Alignment Tool, Discovery Utility, Traceroute, Speed Test
Minimum Software Requirements	Any Modern Web Browser



Radio Sensitivity airMAX AC

5 GHz TX Specifications

Data Rate	Avg Power (dBm)	Tolerance (dB)
1x BPSK ($\frac{1}{2}$)	25	±2
2x QPSK ($\frac{1}{2}$)	25	±2
2x QPSK ($\frac{3}{4}$)	25	±2
4x 16QAM ($\frac{1}{2}$)	25	±2
4x 16QAM ($\frac{3}{4}$)	25	±2
6x 64QAM ($\frac{2}{3}$)	24	±2
6x 64QAM ($\frac{3}{4}$)	22	±2
6x 64QAM ($\frac{5}{6}$)	22	±2
8x 256QAM ($\frac{3}{4}$)	21	±2
8x 256QAM ($\frac{5}{6}$)	21	±2

5 GHz RX Specifications

Data Rate	Avg Power (dBm)	Tolerance (dB)
1x BPSK ($\frac{1}{2}$)	-95	±2
2x QPSK ($\frac{1}{2}$)	-95	±2
2x QPSK ($\frac{3}{4}$)	-93	±2
4x 16QAM ($\frac{1}{2}$)	-90	±2
4x 16QAM ($\frac{3}{4}$)	-86	±2
6x 64QAM ($\frac{2}{3}$)	-83	±2
6x 64QAM ($\frac{3}{4}$)	-77	±2
6x 64QAM ($\frac{5}{6}$)	-74	±2
8x 256QAM ($\frac{3}{4}$)	-69	±2
8x 256QAM ($\frac{5}{6}$)	-66	±2

